

ITCertMagic

ITCertMagic

HOME

ALL VENDORS

★ GUARANTEE

? FAQ

TESTIMONIALS

CART (0)



Try **PDF Demo** before you buy

28 Top Certifications

Apr

- ▶ HP CSE ▶ Avaya Specialist
- ▶ ACE InDesign ▶ LPIC Level1
- ▶ Apple Certified Pro ▶ VCP6-CMA
- ▶ JNCDA ▶ Aruba Certification ▶ CCA XP
- ▶ ICND1 ▶ RCSP ▶ GAQM LCP
- ▶ JNCDS-SEC ▶ Fireware Essentials
- ▶ Oracle Spatial 11g

28 Top Vendors

Apr

- ▶ ISM ▶ HRCI
- ▶ Palo Alto Networks ▶ NSCA
- ▶ SUN ▶ ISQI ▶ Huawei
- ▶ American College ▶ IIA ▶ ARM
- ▶ Pegasystems ▶ OMG ▶ Simens ▶ GRE
- ▶ HAAD ▶ PCI ▶ BBPSD ▶ SCO
- ▶ SugarCRM ▶ Logical Operations ▶ IIBA
- ▶ Altiris ▶ Alfresco ▶ AMA ▶ Informatca

What Client's Say

“ There are some less than 8 new questions, so this 70-695 dump is still mostly valid. Wrote the exams today and passed. ”

 **Timothy**
★★★★★

<http://www.itcertmagic.com/>

Pass-Guaranteed Certification Exam Questions | Exam Dumps - ITCertMagic

Exam : 070-664

Title : TS: Microsoft Lync Server 2010,
Configuring

Vendors : Microsoft

Version : DEMO

1. Your network has Lync Server 2010 deployed.

You configure Call Admission Control.

You need to enable Call Admission Control.

Which cmdlet should you run?

- A. Set-CsBandwidthPolicyServiceConfiguration.
- B. Set-CsMediaConfiguration.
- C. Set-CsNetworkConfiguration.
- D. Set-CsNetworkInterSitePolicy.

Answer: C

2. Your network has a Lync Server 2010 infrastructure that has a bandwidth policy.

You need to override the bandwidth policy for a user named User1.

What should you do first.?

- A. Create a Dial Plan.
- B. Create a Voice Policy.
- C. Create a Client Policy.
- D. Create a Conferencing Policy.

Answer: B

3. Your network has Lync Server 2010 deployed.

You need to ensure that when users on the PSTN receive calls from users in your organization, the calls display the telephone number +14255551212.

What should you do?

- A. From the Lync Server Management Shell, run the Set-CsVoicePolicy cmdlet.
- B. From the Lync Server Management Shell, run the Set-CsCpsConfiguration cmdlet.
- C. From Lync Server 2010 Control Panel, edit the Route settings.
- D. From Lync Server 2010 Control Panel, create a workflow for a Response Group.

Answer: C

4. Your network has a Lync Server 2010 infrastructure that contains three servers. The servers are configured as shown in the following table.

Server name	Server role
Server1	Front End Server
Server2	Mediation Server
Server3	Mediation Server

Server2 and Server3 are in a Mediation pool.

You plan to temporarily remove Server2 from the network.

You need to prevent new voice calls from being routed to Server2.

The solution must not disconnect calls in progress.

What should you do?

- A. From the Lync Server 2010 Control Panel, modify the status of Server2.
- B. From the Lync Server 2010 Control Panel, modify the Voice Routing settings.
- C. From the Lync Server 2010 Topology Builder, edit the properties of the PSTN gateway.
- D. From the Lync Server 2010 Topology Builder, edit the properties of the Mediation pool.

Answer: A

5. Your network has Lync Server 2010 deployed.

You deploy dial-in conferencing.

You need to provide the dial-in conferencing information to all the users on the network.

What should you run?

- A. `Iscmd /server /action:broadcastmessage`
- B. `ocsumutil /ou:users`
- C. the `New-CsAnnouncement cmdlet`
- D. the `Set-CsPinSendCAWelcomeMail cmdlet`

Answer: D

6. Your network has a Lync Server 2010 infrastructure that uses Enterprise Voice.

You need to enable call park for Enterprise Voice users.

You configure a call park number range.

What should you do next?

- A. From the Lync Server 2010 Control Panel, edit the Voice Policy.
- B. From the Lync Server 2010 Topology Builder, edit the Site settings.
- C. From the Lync Management Shell, run the `Set-CsCpsConfiguration cmdlet`.
- D. From the Lync Management Shell, run the `Set-CsVoiceConfiguration cmdlet`.

Answer: C

7. You deploy a Lync Server 2010 pool and a hardware load balancer.

You plan to provide load balancing for dial-in conferencing.

You need to identify which TCP ports must be redirected on the hardware load balancer.

Which TCP ports should you identify?

- A. 80 and 443
- B. 5060 and 5061
- C. 5072 and 5073
- D. 8056 and 8057

Answer: C

8. Your company has a country code of 1 and an area code of 425.

The network has a Lync Server 2010 infrastructure that uses Enterprise Voice.

You plan to create a normalization rule to normalize seven-digit numbers to E.164 format.

You need to identify the appropriate translation rule for the normalization rule.

Which translation rule should you identify?

- A. `+1$1`
- B. `+1425`
- C. `+1425$1`
- D. `$111425`

Answer: C

9. Your company has a telephone number range of (425) 555-1200 to (425) 555-1299.

The country code is 1. The network has Lync Server 2010 deployed.

You need to create a normalization rule for four-digit extension dialing that normalizes extensions to E.164 format.

Which two tasks should you perform? (Each correct answer presents part of the solution. Choose two.)

- A. Set the translation rule to +1425555\$1.
- B. Set the translation rule to +142555512\$1.
- C. Set the translation pattern to match ^4(\d{12})\$.
- D. Set the translation pattern to match A 12(\d{2})\$.

Answer: BD

10. Your network has Lync Server 2010 deployed.

You deploy a Mediation Server, and then you configure a voice route that uses a SIP trunk.

You create a test user named User1.

You enable Enterprise Voice for User1.

You need to verify that when User1 initiates calls to external telephone numbers, the calls are routed through the SIP trunk.

What should you run?

- A. From the Lync server, run the Test-CSMCXPushNotification cmdlet.
- B. From the Lync server, run the New-CsExUmContact cmdlet.
- C. From the Lync server, use the Lync Logging Tool and analyze the trace with Snooper
- D. From the Lync server, use the Lync Control Panel to test voice routing in the Voice Routing tab

Answer: D